

DECLARATION OF PERFORMANCE

Category 3 comprising of
Yellow Stock
Reclamation Yellow Stock
Yellow Multi Stock
Reclamation Yellow Multi Stock

CAT 3 - YS - 2012



Group HD, Category II Handmade Clay Bricks

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION	
Dimensional Tolerances mm	228 x 108 x 68 - 215 x 102.5 x 65		BS EN771-1:2011	
	Tolerance	TM		
	Range	RM		
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm ²	Mean	20.9		
	Category	II		
Dimensional Stability N/mm ²	NPD			
Bond Strength Fixed value N/mm ²	NPD			
Active Soluble Salts	S1			
Reaction to Fire	A1			Commission Decision 2000/605/EC
Water Absorption %	20			BS EN771-1:2011
Water Vapour Permeability	NPD			
Direct Airborne Sound Insulation kg/m ³ (gross)	NPD			
Thermal Properties	NPD			
Durability Against Freeze Thaw	F2			
Dangerous Substances	NPD			

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

July 2012

Imperial Bricks
 Grindle House Farm
 Grindle Road
 Grindle, Near Shifnal
 Shropshire
 TF11 9JR