

TECHNICAL INFORMATION

CATEGORY 19 COMPRISING OF

BRICK NAME Antique Multi Waterstruck

BRICK TYPE Through colour clay waterstruck brick

SPECIFICATION Manufactured to BS EN 771-1:2011

SIZE* 215 x 102.5 x 65mm

DIMENSIONAL TOLERANCE: T2

COMPRESSIVE STRENGTH 25 N/MM²

WATER ABSORPTION 10 - 12%

SOLUBLE SALT CLASSIFICATION S2

PACKAGING Shrink wrapped on wooden pallets in packs of 336

PACK SIZE; LxWxH 910 x 910 x 925mm Approx.

PACK WEIGHT 0.87 Tonnes Approx.

USAGE Always mix from several packs, working vertically down

the blades, not horizontally across the tops of the packs

SAMPLES Samples will be supplied on request

DURABILITY F2

PERFORMANCE The recommendations of good practice made in the relevant

British Standards regarding design and workmanship must be

fully observed.

Liability cannot be accepted for the performance of the

product if used outside our recommendations.

Guidance on the use of these bricks in specific situations

is readily available from us.

03.2019



^{*}Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in the relevant European Standard.