

DECLARATION OF PERFORMANCE

Category 13 comprising of
Red Waterstruck
Restoration Red Waterstruck
Oxford Yellow Multi Waterstruck
Restoration Oxford Yellow Waterstruck
Lightly Weathered Waterstruck

CAT 13 - WS - 2016

Group HD, Category II Handmade Clay Bricks



Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION	
Dimensional Tolerances mm	228 x 108 x 68 – 228 x 108 x 73		
	Tolerance	T1	
	Range	R1	
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm ²	Mean	12.9	
	Category	II	
Dimensional Stability	NPD	BS EN771-1:2011	
Bond Strength Fixed value N/mm ²	NPD		
Active Soluble Salts	S2		
Reaction to Fire	A1		Commission Decision 2000/605/EC
Water Absorption %	13		
Water Vapour Permeability	NPD	BS EN771-1:2011	
Direct Airborne Sound Insulation kg/m ³ (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

July 2016

Imperial Bricks
 Grindle House Farm
 Grindle Road
 Grindle, Near Shifnal
 Shropshire
 TF11 9JR