



TECHNICAL INFORMATION

BRICK NAME	CATEGORY 30 COMPRISING OF: Imperial Accrington Smooth Red
BRICK TYPE	Through colour clay extruded brick
SPECIFICATION	Manufactured to EN 771-1:2011+A1 :2015
SIZE*	80 x 230 x 108mm 75 x 230 x 108mm
DIMENSIONAL TOLERANCE	T2
RANGE	R2
COMPRESSIVE STRENGTH	125 N/MM ²
WATER ABSORPTION	4.5%
SOLUBLE SALT CLASSIFICATION	S2
PACKAGING	Shrink wrapped on wooden pallets in packs of 504
PACK SIZE; LxWxH	1100 x 1100 x 1100mm Approx.
PACK WEIGHT	1.2 Tonnes Approx.
USAGE	Always mix from several packs, working vertically down the blades, not horizontally across the tops of the packs.
SAMPLES	Samples will be supplied on request.
DURABILITY	F2
PERFORMANCE	The recommendations of good practice made in the relevant British Standards regarding design and workmanship must be fully observed. Liability cannot be accepted for the performance of the product if used outside our recommendations. Guidance on the use of these bricks in specific situations is readily available from us.

*Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in the relevant European Standard.

