

## DECLARATION OF PERFORMANCE

**Category 21 comprising of**  
**Country Blend (Gas Fired)**  
**Farmhouse Orange (Gas Fired)**  
**Urban Weathered (Gas Fired)**  
**Reclamation Shire Blend (Gas Fired)**  
**3" Country Blend**  
**3" Olde Reclamation Clamp**

CAT 21 - 2019



**Group HD, Category II Handmade Clay Bricks**

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION	
Dimensional Tolerances mm	230 x 110 x 68 230 x 110 x 73 *215 x 102.5 x 65		BS EN771-1	
	Tolerance	T1* / TM		
	Range	R1 / RM*		
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm <sup>2</sup>	Mean	52.3		
	Category	II		
Dimensional Stability N/mm <sup>2</sup>	NPD			
Bond Strength Fixed value N/mm <sup>2</sup>	NPD			
Active Soluble Salts	S2			
Reaction to Fire	A1			Commission Decision 2000/605/EC
Water Absorption %	11.9			BS EN771-1
Water Vapour Permeability	NPD			
Direct Airborne Sound Insulation kg/m <sup>3</sup> (gross)	NPD			
Thermal Properties	NPD			
Durability Against Freeze Thaw	F2			
Dangerous Substances	NPD			

**The performance of the product(s) identified above is in conformity with the declared values**

Signed for and on behalf of the manufacturer by:

**Jason Hughes, Managing Director**

January 2019

Imperial Bricks  
 Grindle House Farm  
 Grindle Road  
 Grindle, Near Shifnal  
 Shropshire  
 TF11 9JR