

## DECLARATION OF PERFORMANCE

Category 22 comprising of

York Clamp

CAT 22 - YC - 2018

Group HD, Category II Handmade Clay Bricks



Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Dimensional Tolerances mm	230 x 110 x 73 - 215 x 102.5 x 65		BS EN771-1:2011
	Tolerance	T1	
	Range	R1	
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm <sup>2</sup>	Mean	24.3	
	Category	II	
Dimensional Stability	NPD		
Bond Strength Fixed value N/mm <sup>2</sup>	NPD		
Active Soluble Salts	S2		
Reaction to Fire	A1	Commission Decision 2000/605/EC	
Water Absorption %	13	BS EN771-1:2011	
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m <sup>3</sup> (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

**The performance of the product(s) identified above is in conformity with the declared values**

Signed for and on behalf of the manufacturer by:

**Jason Hughes, Managing Director**

August 2018

Imperial Bricks Ltd  
Grindle House Farm  
Grindle Road  
Grindle, Near Shifnal  
Shropshire  
TF11 9JR